

HOTLINE: 097.790.3839

HELI
LIFTING THE FUTURE




TOP1 FORKLIFT MANUFACTURER AND SALER
IN CHINA FOR CONSECUTIVE 24 YEARS

CQDH13/14-850

1.3/1.4 Ton Scissor Stacker

Load Curve



Advantages

Configuration and Performance

- Electronic power steering system, light and low noise.
- Two-way magnetic valve, three drop speed mode.
- AC Driving system, No carbon brush, maintenance free.
- USA CURTIS driving controller.
- Electromagnetic, regenerative braking system.
- Lifting, reach, regenerative limit, motor and battery life extension.
- Equipped with double oil cylinder, fork tilt more smoothly.
- Standard moon walk. Handle at any angle, the vehicle goes straight.

Safety

- Curve automatic deceleration devices, more safe.
- Stepless speed control system, safe and quiet.
- Controller with Multiple automatic protection.
- Emergency reversing device/Emergency brake switch.
- High position automatic reduction device.



AC | EPS | Moon Walk
Down mode at 3speeds

Type	Lift height (mm)	Outside width between forks (mm)	Inside width between forks (mm)
CQDH13-850	3800/4000/4500/5000/5500	1270/1420/1470	1070/1220/1270
CQDH14-850	3800/4000/4500/5000/5500	1270/1420/1470	1070/1220/1270

HELI CQDH13/14-850

Feature			
Model		CQDH13	CQDH14
Configuration No.		850	850
Type		Reach(Tilt,Side shifter)	Reach(Tilt)
Mast type		Standard 3-Stage	Standard 3-Stage
Load capacity	kg	1300	1400
Load center	mm	500	500
Wheel base	mm	1478	1478
Operating type		Walkie	Walkie
Wheels			
Wheels type		PU	PU
Wheel quantity Driving wheel/ Balance wheel/Bearing wheel		1/4	1/4
Dimension			
Reach distance	mm	0-550	0-550
Standard lift height	mm	3800/4000/4500/5000/5500	3800/4000/4500/5000/5500
Max.extend height	mm	4991/5191/5691/6191/6691	4991/5191/5691/6191/6691
Mast lowered height	mm	1914/2081/2248/2415/2582	1914/2081/2248/2415/2582
Lowered fork height	mm	55	55
Fork size(length/width/thickness)	mm	1070/100/40	1070/100/40
Overall length	mm	2225	2225
Overall width	mm	1430	1430
Outside width between forks	mm	200-755	200-755
Distance shift fork side	mm	150	-
Tilt of fork(F/B)	mm	4/3	4/3
Min.Turning radius		1566	1566
Min.Aisle width for pallets 800×1200	km/h	2135	2135
Min.Aisle width for pallets 1000×1200	mm/s	2315	2315
Min.ground clearance	mm/s	30	30
Performance			
Travel speed,laden/unladen		3.5/4	3.5/4
Lift speed,laden/unladen	kW	130/230	130/230
Lowering speed,laden/unladen	V	130/230	130/230
Gradeability,laden/unladen	Ah	3/5	3/5
Electrical configuration			
Drive motor/Lift motor/Steering motor		AC1.5/DC3.0/DC0.15	AC1.5/DC3.0/DC0.15
Battery voltage		24	24
Battery capacity	kg	345 (Options:FAAM345)	345 (Options:FAAM345)
Brake	kg	Electromagnetic/Regenerative	Electromagnetic/Regenerative
Controller		CURTIS	CURTIS
Weight			
Battery weight		300	300
Service weight with battery		2420	2400

* Details of specifications and equipment are based on information available at time of printing and may change without notice.

CÔNG TY TNHH XE NÀNG BÌNH MIINH

Mr Hoàng: 097.790.3839

Email: hoangnguyen3888@gmail.com

Website: http://xenangheli.com

Trụ sở: Số 763, đường Nguyễn Văn Linh, phường Sài Đồng, quận Long Biên, tp Hà Nội

Chi nhánh: 288/2, Quốc lộ 1A, phường Thới An, quận 12, tp Hồ Chí Minh

Chi nhánh: Khu phố Bình Đường 2, phường An Bình, thị xã Dĩ An, tỉnh Bình Dương

Chi nhánh: Số 1, đường Nguyễn Văn Linh, phường Hải Châu, tp Đà Nẵng

ĐẠI LÝ CHÍNH HÃNG XE NÀNG HÀNG HELI